

## DISPOSABLE PULL-ON UNDERGARMENT

## BACKGROUND OF THE INVENTION

This invention relates to a disposable pull-on undergarment and more particularly to undergarment such as a disposable pull-on diaper, training pants or incontinent pants.

Japanese Patent Application Publication No. 1997-38134A describes a disposable pull-on undergarment comprising a liquid-pervious topsheet, a liquid-impervious backsheet and a liquid-absorbent core disposed between these two sheets so as to configure front and rear waist regions and a crotch region extending between these two waist regions wherein the waist regions are connected with each other in bonding zones extending along transversely opposite side edge portions of the respective waist regions and thereby a waist-opening and a pair of leg-openings are defined. In each of the bonding zones, a plurality of welding lines are intermittently arranged to be spaced one from another by a predetermined distance longitudinally of the undergarment.

To take off the used undergarment, the front and rear waist regions may be pulled in opposite directions to tear off the undergarment along the bonding zones from the waist-opening toward the leg-openings.

The undergarment is provided with circumferentially stretchable first elastic members bonded under tension to peripheral edge of the waist-opening and with circumferentially stretchable second elastic members bonded under tension to respective peripheral edges of the leg-openings. Circumferentially stretchable third elastic members are bonded under tension to the front and rear waist regions so as to extend across these waist regions.

Each of these elastic members has longitudinally opposite end portions and an intermediate portion. In the case of the first and second elastic members, the opposite end portions and intermediate portion are disposed between the top- and backsheets and intermittently bonded to inner surface of at least one of these sheets by means of adhesive. In the case of the third elastic members, the respective opposite end portions are disposed between the top- and backsheets and intermittently bonded to inner surface of at least one of these sheets by means of adhesive while the intermediate portion is intermittently bonded to inner surface of the backsheet by means of adhesive. The respective opposite end portions of these elastic members partially lie in the bonding zones. The intermediate portion of the third elastic members circumferentially extend across the core.

00064622 052404  
FOI250-22949860

In the undergarment disclosed in the Publication, the opposite end portions of the first - third elastic members partially lie in the bonding zones and may prevent the used undergarment from being smoothly torn off along the bonding zones.

#### SUMMARY OF THE INVENTION

Sub  
A1  
It is an object of this invention to provide the disposable pull-on undergarment improved to be smoothly torn off along the bonding zones.

According to this invention, there is provided a disposable pull-on undergarment having first and second waist regions opposed to each other and a crotch region extending between these two waist regions wherein these first and second waist regions are connected with each other in bonding zones extending along transversely opposite side edge portions thereof so as to define a waist-opening and a pair of leg-openings and wherein first elastic members being stretchable circumferentially of the waist regions are bonded under tension to peripheral edge of the waist-opening and second elastic members being stretchable circumferentially of the legs are bonded under tension to peripheral edges of the leg-openings.

Sub  
A2  
The improvement according to this invention is in that

0985463-054404  
104250-2294960

the first elastic members respectively have first opposite ends and first intermediate portions extending between the first opposite ends, respectively, and the first opposite ends are positioned and fixed at first zones defined immediately inside the bonding zones in a circumferential direction of the waist-opening.

According to one preferred embodiment of this invention, the second elastic members respectively have second opposite ends and second intermediate portions extending between the second opposite ends, respectively, and the second opposite ends are positioned and fixed at second zones defined immediately inside the bonding zones in respective circumferential directions of the leg-openings.

According to another preferred embodiment of this invention, at least one third elastic member lying below the first elastic members and being stretchable in the circumferential direction of the waist-opening is attached under tension to at least one of the first and second waist regions between the peripheral edge of the waist-opening and the peripheral edges of the leg-openings and wherein the third elastic member has third opposite ends and third intermediate portions extending between the third opposite ends and the third opposite ends are positioned and fixed at third zones defined

1. 34250 22949360

Sub  
22  
10/1

immediately inside the bonding zones in the circumferential direction of the waist-opening.

According to still another preferred embodiment of this invention, a peel strength between the first and second waist regions in the bonding zones is in a range of 4 - 40 N with respect to 25 mm; a longitudinal dimension of the bonding zone.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view showing a disposable diaper as a typical embodiment of this invention as viewed from the side a front waist region and partially broken away;

Fig. 2 is an exploded plan view showing the diaper of Fig. 1 as viewed from the side of a backsheet;

Fig. 3 is a sectional view taken along line A - A in Fig. 2;

Fig. 4 is a perspective view showing another embodiment of the diaper according to the invention as viewed from the side of the front waist region and partially broken away;

Fig. 5 is an exploded plan view showing the diaper of Fig. 4 as viewed from the side of the backsheet; and

Fig. 6 is a sectional view taken along line B - B in Fig. 5.

FOR 250-22949360

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Details of a disposable pull-on undergarment according to this invention will be more fully understood from the description of a disposable pull-on diaper as one embodiment given hereunder with reference to the accompanying drawings.

Fig. 1 is a perspective view showing a disposable diaper 1 as viewed from the side of a front waist region 20 and partially broken away, Fig. 2 is an exploded plan view of the diaper 1 shown by Fig. 1 as viewed from the side of a backsheet 3 and Fig. 3 is a sectional view taken along line A - A in Fig. 2.

The diaper 1 basically comprises a liquid-pervious topsheet 2, a liquid-impervious backsheet 3 and a liquid-absorbent core 4 disposed between the top- and backsheets 2, 3. The liquid-absorbent core 4 has its entire surface covered with and bonded to liquid-pervious tissue paper (not shown) and the core 4 is bonded to inner surface of at least one of the top- and backsheets 2, 3 via the tissue paper.

As seen in Fig. 2, the diaper 1 has a front waist region 20 (first waist region), a rear waist region 22 (second waist region) and a crotch region 21 extending between the front and rear waist regions 20, 22. The diaper 1 is contoured by transversely opposite side edge portions 1a curving transversely inward to describe circular arcs and

104250" 2294380

longitudinally opposite edge portions 1b extending parallel transversely of the diaper 1. Portions of the top- and backsheets 2, 3 extending outward beyond peripheral edge of the core 4 are placed upon and bonded to each other. Bonding zones B1 extend along the respective transversely opposite side edge portions 1a of the top- and backsheets 2, 3. Each of the bonding zones B1 comprises a plurality of welding lines 7 intermittently arranged so as to be spaced one from another by a predetermined distance longitudinally of the diaper 1. Of the diaper 1, the bonding zones B1 are illustrated to be defined between imaginary lines 2 and the adjacent side edges 1c of the front and rear waist regions 20, 22 and to contain therebetween the welding lines 7.

The respective side edge portions 1a of the front and rear waist regions 20, 22 put flat together are bonded together in the respective bonding zones B1 to define a waist-opening 5 opening upward as viewed in Fig. 1 and a pair of leg-openings 6 opening right- and leftward, respectively, as viewed in Fig. 1.

A plurality of elastically stretchable elements 8 (first elastic member) circumferentially extending in a direction X are bonded under tension to peripheral edge of the waist-opening 5. Similarly, a plurality of elastically stretchable elements

TOP SECRET

9 (second elastic member) circumferentially extending in a direction Y are bonded under tension to respective peripheral edges of the leg-openings 6.

Sub A3 The elastic members 8 associated with the waist-opening have their longitudinally opposite ends 8a (first opposite ends) lying in the transversely opposite side edge portions 1a of the front and rear waist regions 20, 22 and an intermediate portions 8b (first intermediate portion) extending between the respective opposite ends 8a. The respective opposite ends 8a are positioned in zones B2 defined immediately inside the respective bonding zones B1 in the circumferential direction X. The elastic members 8 is disposed between the top- and backsheets 2, 3 with their respective opposite ends 8a partially fixed to inner surfaces of these sheets 2, 3 in the respective zones B2 by means of adhesive 10 and with their intermediate portions 8b intermittently fixed to inner surfaces of these sheets 2, 3 by means of adhesive 11.

Sub A4 The elastic member 9 associated with each of the leg-openings has longitudinally opposite ends 9a (second opposite ends) lying in the transversely opposite side edge portions 1a of the front and rear waist regions 20, 22, respectively, and an intermediate portion 9b (second intermediate portion) extending between the opposite ends 9a. The opposite ends 9a

FOIA b7 - E294360



are positioned in zones B3 defined immediately inside the respective bonding zones B1 in the circumferential direction Y. The elastic members 9 are disposed between the top- and backsheets 2, 3 with their respective opposite ends 9a partially fixed to inner surfaces of these sheets 2, 3 in the respective zones B3 by means of adhesive 12 and with their intermediate portions 9b intermittently fixed to the inner surfaces of these sheets 2, 3 by means of adhesive 13.

In the presence of these elastic members 8, 9 incorporated in the diaper 1, the peripheral edge of the waist-opening 5 has a stretchability in its circumferential direction X and the peripheral edges of the leg-openings 6 have a stretchability in their circumferential direction Y. Referring to Fig. 1, a plurality of gathers are formed along the respective peripheral edges of the waist-opening 5 and the leg-openings 6 as the elastic members 8, 9 contract.

Preferably, the respective opposite ends 8a, 9a of the elastic members 8, 9 are firmly fixed to the inner surfaces of the top- and backsheets 2, 3 in order to prevent these opposite ends 8a, 9a from being unintentionally peeled off from the top- and backsheets 3 during use of the diaper 1.

To take the diaper 1 from a wearer's body, the diaper 1 may be torn off along the bonding zones B1 from the waist-opening

704250 2243860

5 toward the leg-openings 6. The respective opposite ends 8a, 9a of the elastic members 8, 9 are not present in the bonding zones B1 and therefore only a peel strength of the bonding zones B1 in the welded lines 7 resist operation of tearing off the diaper 1 along the bonding zones B1.

The peel strength of the diaper 1 in the bonding zones B1 is in a range of 4 - 40 N with respect to 25 mm, a longitudinal dimension of the bonding zone B1. The peel strength less than 4 N/25 mm might unintentionally separate the front and rear waist regions along the bonding zones B1 as a tensile force tending to enlarge the peripheral edge of the waist-opening and the peripheral edges of the leg-openings is exerted on the diaper 1. The peel strength exceeding 40 N/25 mm might require a remarkable force to tear off the diaper 1 along the bonding zones B1.

Fig. 4 is a perspective view showing another embodiment of the diaper 1 as viewed from the side of the front waist region 20 and partially broken away, Fig. 5 is an exploded plan view showing the diaper 1 of Fig. 4 as viewed from the side of the rear waist region and Fig. 6 is a sectional view taken along line B - B in Fig. 5.

The diaper 1 comprises a liquid-pervious topsheet 2, a liquid-impervious backsheet 3 and a liquid-absorbent core 4

104453 2349860

having its entire surface being covered with and bonded to water-pervious tissue paper (not shown). These sheets 2, 3 and core 4 configure together a front waist region 20 (first waist region), a rear waist region 22 (second waist region) and a crotch region 21 extending between the front and rear waist regions 20, 22. The diaper 1 is contoured by transversely opposite side edge portions 1a longitudinally extending partially parallel to each other and partially curved inward transversely of the diaper 1 to describe circular arcs and longitudinally opposite edge portions 1b transversely extending parallel to each other.

The transversely opposite side edge portions 1a of the front and rear waist regions 20, 22 put flat together are bonded together in the bonding zones B1 to define a waist-opening 5 opening upward as viewed in Fig. 4 and a pair of leg-openings 6 opening right- and leftward as viewed in Fig. 4.

The diaper 1 Fig. 4 is distinguished from the diaper 1 of Fig. 1 in that the adhesive 17 is applied in the form of dots as will be best seen in Fig. 5. In this diaper 1, the bonding zones B1 are defined between imaginary lines Z and the adjacent side edges 1c of the front and rear waist regions 20, 22 and these bonding zones B1 are coated with the dot-like adhesive 17.

Sub  
A5

The front and rear waist regions 20, 22 of the diaper 1 are provided with, in addition to the elastic members 8 associated with the waist-opening (first elastic members) and the elastic members 9 associated under the leg-openings, a plurality of auxiliary elastic members 14 (third elastic members) are positioned and fixed under tension to the diaper 1 below the elastic members associated with the waist-opening so as to extend in its circumferential direction X. The auxiliary elastic members 14 are attached to the front and rear waist regions 20, 22 and extend across the core 4 in the circumferential direction X of the waist-opening.

The auxiliary elastic members 14 respectively have opposite ends 14a (third opposite ends) lying on the respective opposite side edge portions 1a and intermediate portions 14b (third intermediate portions) extending between the respective opposite ends 14a. The respective opposite ends 14a are positioned in zones (B4) (third zones) defined immediately inside the respective bonding zones B1 in the circumferential direction of the waist-opening. The respective opposite ends 14a of the auxiliary elastic members 14 are disposed between the top- and backsheets 2, 3 and partially fixed to the inner surfaces of these sheets 2, 3 by means of adhesive 15. The respective intermediate portions 14b are disposed between the

104230" E234380

In the presence of these elastic members 8, 9, 14 incorporated in the diaper 1, the peripheral edge of the waist-opening 5 has a stretchability in its circumferential direction X and the peripheral edges of the leg-openings 6 have a stretchability in their circumferential direction Y. Referring to Fig. 4, a plurality of gathers are formed with the respective peripheral edges of the waist-opening 5 and the leg-openings 6 as the elastic members 8, 9, 14 contract.

To eliminate an anxiety that the opposite ends 8a, 9a, 14a of the respective elastic members 8, 9, 14 might be peeled off from the top- and backsheets 2, 3, these opposite ends 8a, 9a, 14a should be firmly bonded to the respective inner surfaces of the top- and backsheets 2, 3.

Sub  
Ala

Sub  
A4

2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2811 2812 2813 2814 2815 2816 2817 2

The nonwoven fabric used for this invention may be of various types such as spun lace-, needle punch-, melt blown-, thermal bond-, spun bond- and chemical bond-types. The component fiber may be selected from a group including

polyolefine-based fiber, polyester-based fiber, polyamide-based fiber and thick-and-thin type or side-by-side type conjugated fiber of polyethylene/polypropylene or polyester.

The elastic members 8, 9, 14 may be formed with thread-, filament-, film- or ribbon-like elastomer of natural or synthetic rubber. The elastic members 8 associated with the waist-opening and the elastic members 9 associated with the respective leg-openings in the diaper 1 illustrated by Figs. 1 and 4 may be alternatively arranged. According to this alternative embodiment, the respective opposite ends 8a, 9a of these elastic members 8, 9 may be continuously fixed to the inner surfaces of the top- and backsheets 2, 3 by means of adhesive 10, 12, respectively, in the zones B2, B3 and the intermediate portions 8b, 9b of these elastic members 8, 9 may be also continuously fixed to the inner surfaces of the top- and backsheets 2, 3 by means of adhesive 11, 13, respectively. The auxiliary elastic members 14 in the diaper 1 illustrated by Fig. 4 may be also alternatively arranged. According to this alternative embodiment, the respective opposite ends 14a of the auxiliary elastic members 14 may be continuously fixed to the inner surfaces of the top- and backsheets 2, 3 in the zones B4 by means of adhesive 15 and their intermediate portions 14b may be continuously fixed to the inner surfaces of the backsheet

00364523-05240  
104250-2294360

3 and the core 4, at least of the backsheet 3 by means of adhesive 16.

The core 4 comprises a mixture of fluff pulp obtained by crushing wood pulp and high absorption polymer grains compressed to a desired thickness. The high absorption polymer may be selected from a group including graft polymer of starch, modified cellulose, crosslinked water-soluble polymer and self-crosslinked alkali metal acrylate.

Bonding the sheets 2, 3 to each other or to the core 4 may be carried out by means of suitable adhesive such as hot melt adhesive or pressure-sensitive adhesive, or using suitable welding technique such as heat sealing or supersonic sealing technique. Hot melt adhesive is particularly preferable as the adhesive means 10, 11, 12, 13, 15, 16, 17. In addition to adhesive means 10, 11, 12, 13, 15, 16, 17, the technique of welding may be also used for the purpose of fixation of the elastic members 8, 9, 14.

This invention is not limited to a disposable diaper but applicable also to the other disposable pull-on undergarment such as training pants or incontinent pants.

In the disposable pull-on undergarment according to this invention, the respective opposite ends of the elastic members are positioned and fixed in the zones defined immediately inside

104250 22549360



the bonding zones in the circumferential directions of the waist- and leg-openings, respectively. Such unique arrangement enables the used wearing article to be smoothly torn off along the bonding zones without being resisted by the respective opposite ends of the elastic members.

Furthermore, the disposable pull-on undergarment according to this invention has a peel strength along the bonding zones adjusted to 4 - 40 N with respect to 25 mm, a longitudinal dimension of the bonding zone. With an advantageous consequence, it is not apprehended that the disposable pull-on undergarment might be unintentionally peeled off along the bonding zones, on one hand, and no troublesome effort is necessary to tear off the used pull-on undergarment along the bonding zones, on the other hand.

09564522979860  
FOI# 22979860